



# Smart Projector Solusi Kerja di Masa Pandemi

Hybrid Working dan Hybrid Meeting Lebih Mudah dengan Smart Projector



Scan Disini



@officialbenq\_id



BenQ Indonesia



BenQ Teknologi Indonesia



**Kamera DVY21**

Kamera tambahan untuk  
Solusi Video Conference



Wireless



Video Conference



Android



USB Plug & Play



AMS



DMS



X-Sign Broadcasting



Aksesibilitas  
Nirkabel



Aksesibilitas  
Aplikasi



Mirroring  
Nirkabel



Sistem Android  
Internal



Garansi 3 Tahun

# Smart Projector untuk Bisnis



Model Name		EH600	EW600	EX600	EW800ST	EX800ST
Display	Native Resolution	1920 x 1080 pixels, 1080p	1280 x 800 pixels, WXGA	1024 x 768 pixels, XGA	1280x800 pixels, WXGA	1024 x 768 pixels, XGA
	Brightness	3,500 Lumens	3,600 Lumens	3,600 Lumens	3,300 Lumens	3,300 Lumens
	Contrast Ratio*	20,000:1	20,000:1	20,000:1	20,000:1	20,000:1
	Display Color	1.07 Billion Colors	1.07 Billion Colors	1.07 Billion Colors	1.07 Billion Colors	1.07 Billion Colors
	Aspect Ratio	Native 16:9 (5 aspect ratio selectable)	Native 16:10 (5 aspect ratio selectable)	Native 4:3 (5 aspect ratio selectable)	Native 16:10 (5 aspect ratio selectable)	Native 4:3 (5 aspect ratio selectable)
	Light Source	Lamp 200W	Lamp 200W	Lamp 200W	Lamp 200W	Lamp 200W
Optical	Light Source Life*	Normal 5000 hrs; Economic 10000 hrs; SmartEco 10000 hrs; LampSave 15000 hrs	Normal 5000 hrs; Economic 10000 hrs; SmartEco 10000 hrs; LampSave 15000 hrs	Normal 5000 hrs; Economic 10000 hrs; SmartEco 10000 hrs; LampSave 15000 hrs	Normal 5000 hrs; Economic 10000 hrs; SmartEco 10000 hrs; LampSave 15000 hrs	Normal 5000 hrs; Economic 10000 hrs; SmartEco 10000 hrs; LampSave 15000 hrs
	Throw Ratio	1.49~1.64	1.55~1.7	1.96~2.15	0.49	0.61
	Zoom Ratio	1.1X	1.1X	1.1X	Fixed	Fixed
	Lens Control	Manual Focus	Manual Focus	Manual Focus	Manual Focus	Manual Focus
	Keystone Correction	ID, Vertical +/- 40 degrees	ID, Vertical +/- 40 degrees	ID, Vertical +/- 40 degrees	ID, Vertical ± 30 degrees	ID, Vertical ± 30 degrees
	Projection Offset	108±2.5% ( Full-Height)	100±2.5% ( Full-Height)	110±2.5% ( Full-Height)	105±2.5% ( Full-Height)	115±2.5% ( Full-Height)
Audio	Built-in Speaker	2W x1	2W x1	2W x1	2W x1	2W x1
Security	Security	Security Bar	Security Bar	Security Bar	Security Bar, Kensington anti-theft lock slot	Security Bar, Kensington anti-theft lock slot
Connectivity	I/O Port	HDMI x1 PC (D-sub 15pin) x1 Monitor out (D-sub 15pin, Female) x1 Audio in (mini jack) x1 Audio out (mini jack) x1 RS232 In (D-sub 9pin, male) x1 USB Type A-I x1 USB Type A-2 (5V, 1.5A) x1 USB Type A (For hidden wireless dongle) x1 USB Type mini B x1 IR Receiver (Front+Top) x2	HDMI x1 PC (D-sub 15pin) x1 Monitor out (D-sub 15pin, Female) x1 Audio in (mini jack) x1 Audio out (mini jack) x1 RS232 In (D-sub 9pin, male) x1 USB Type A-I x1 USB Type A-2 (5V, 1.5A) x1 USB Type A (For hidden wireless dongle) x1 USB Type mini B x1 IR Receiver (Front+Top) x2	HDMI x1 PC (D-sub 15pin) x1 Monitor out (D-sub 15pin, Female) x1 Audio in (mini jack) x1 Audio out (mini jack) x1 RS232 In (D-sub 9pin, male) x1 USB Type A-I x1 USB Type A-2 (5V, 1.5A) x1 USB Type A (For hidden wireless dongle) x1 USB Type mini B x1 IR Receiver (Front+Top) x2	HDMI x1 PC (D-sub 15pin) x1 Monitor out (D-sub 15pin, Female) x1 Audio in (mini jack) x1 Audio out (mini jack) x1 RS232 In (D-sub 9pin, male) x1 LAN Port (RJ45 for Network ) x1 USB Type A-I x1 USB Type A-2 (5V, 1.5A) x1 USB Type mini B x1 IR Receiver (Front+Top) x2	HDMI x1 PC (D-sub 15pin) x1 Monitor out (D-sub 15pin, Female) x1 Audio in (mini jack) x1 Audio out (mini jack) x1 RS232 In (D-sub 9pin, male) x1 LAN Port (RJ45 for Network ) x1 USB Type A-I x1 USB Type A-2 (5V, 1.5A) x1 USB Type mini B x1 IR Receiver (Front+Top) x2
	Smart System	OS System	Android 6.0	Android 6.0	Android 6.0	Android 6.0
Wireless	ROM/RAM	16GB/2GB	16GB/2GB	16GB/2GB	16GB/2GB	16GB/2GB
	Wireless	Dual Band 802.11ac/ b/g/n, 2.4G/5G	Dual Band 802.11ac/ b/g/n, 2.4G/5G	Dual Band 802.11ac/ b/g/n, 2.4G/5G	Dual Band 802.11ac/ b/g/n, 2.4G/5G	Dual Band 802.11ac/ b/g/n, 2.4G/5G
Compatibility	Bluetooth	4.0	4.0	4.0	4.0	4.0
	Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200)	VGA(640 x 480) to WUXGA_RB(1920 x 1200)	VGA(640 x 480) to WUXGA_RB(1920 x 1200)	VGA(640 x 480) to WUXGA_RB(1920 x 1200)	VGA(640 x 480) to WUXGA_RB(1920 x 1200)
	HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p	480i, 480p, 576i, 567p, 720p, 1080i, 1080p	480i, 480p, 576i, 567p, 720p, 1080i, 1080p	480i, 480p, 576i, 567p, 720p, 1080i, 1080p	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
Power	Video Compatibility	NTSC, PAL, SECAM	NTSC, PAL, SECAM	NTSC, PAL, SECAM	NTSC, PAL, SECAM	NTSC, PAL, SECAM
	Power Consumptions (Max/Normal/Eco)	Max 320W. Normal 280 W. Eco 235 W.	Max 320W. Normal 280 W. Eco 235 W.	Max 320W. Normal 280 W. Eco 235 W.	Max 320W. Normal 280 W. Eco 235 W.	Max 320W. Normal 280 W. Eco 235 W.
	Standby Power consumption	Normal < 0.5W	Normal < 0.5W	Normal < 0.5W	Normal < 0.5Watts. Network < 2W.	Normal < 0.5Watts. Network < 2W.
Dimension and Weight	Power Supply	100 ~ 240V AC	100 ~ 240V AC	100 ~ 240V AC	100 ~ 240V AC	100 ~ 240V AC
	Product Dimensions (WxHxD)	296 x 120 x 232 mm	296 x 120 x 232 mm	296 x 120 x 232 mm	296 x 120 x 250 mm	296 x 120 x 250 mm
Operation Condition	Product Weight	2.5 Kg	2.5 Kg	2.5 Kg	2.6 Kg+/- 200g	2.6 Kg+/- 200g
	Noise Level (Normal/Eco)	33/29 dBA	33/29 dBA	33/29 dBA	33/29 dBA	33/29 dBA
Accessories	Accessories (Standard)	Wireless Dongle: WDR02U Power Cord (by region) Remote Control w/ Battery (RCI023) VGA cable Warranty Card (by region) QSG	Wireless Dongle: WDR02U Power Cord (by region) Remote Control w/ Battery (RCI023) VGA cable Warranty Card (by region) QSG	Wireless Dongle: WDR02U Power Cord (by region) Remote Control w/ Battery (RCI023) VGA cable Warranty Card (by region) QSG	Wireless Dongle: WDR02U Power Cord (by region) Remote Control w/ Battery (RCI023) VGA cable Warranty Card (by region) QSG	Wireless Dongle: WDR02U Power Cord (by region) Remote Control w/ Battery (RCI023) VGA cable Warranty Card (by region) QSG
	Accessories (Optional)	Spare Lamp Kit (5J.JLV05.001) 3D Glasses (5J.J9H25.002) Ceiling mount (5J.JAM10.001)	Spare Lamp Kit (5J.JLT05.001) 3D Glasses (5J.J9H25.002) Ceiling mount (5J.JAM10.001)	Spare Lamp Kit (5J.JLR05.001) 3D Glasses (5J.J9H25.002) Ceiling mount (5J.JAM10.001)	Spare Lamp Kit (5J.JLT05.001) 3D Glasses (5J.J9H25.002) Wall mount (WM06G3)	Spare Lamp Kit (5J.JLT05.001) 3D Glasses (5J.J9H25.002) Wall mount (WM06G3)
OSD	On Screen Display Language	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/Thai/TraditionalChinese/Vietnamese /Farsi (30 Languages)				

## PT. BenQ Teknologi Indonesia

Wisma 77 Tower 2, 5<sup>th</sup> Floor  
 Jl. Letjen S. Parman Kav. 77, Slipi – West Jakarta 11410  
 Phone: +62-21-2967-5967; +62-21-2967-5968 Website: [www.BenQ.co.id](http://www.BenQ.co.id)