

Connecting Workspaces


Bring your meetings to life with BenQ video conferencing solutions. Experience unmatched audio and video fidelity for any meeting space.



DVY21 1080P Meeting Room Webcam

- 88° wide field of view
- Clear Full HD video
- Omnidirectional microphones with noise suppression
- Adjusts to lighting conditions
- USB plug and play


| Suggested setup |



DVY22 4K Digital Zoom Conference Camera

- 126° wide field of view
- 4x digital zoom
- AI-powered auto framing
- Omnidirectional microphones with noise suppression
- Dual-stream support
- Super low-light performance
- USB 3.0 plug and play


| Suggested setup |



DVY23 1080P PTZ Conference Camera

- Ultra-detailed 20x optical zoom
- Pan: $\pm 170^\circ$ | Tilt: -30° to $+90^\circ$
- Video outputs: USB 3.0, HDMI, 1GbE with PoE, 3G-SDI
- Streaming: RTSP and RTMP
- Control ports: RS232, RS422, RS485, LAN, and remote control
- USB 3.0 plug and play

| Suggested setup |



Because it matters



Models	DVY21	DVY22	DVY23
Camera			
Dimensions (H × W × D)	30 mm × 102 mm × 46 mm (1.18 in × 4.02 in × 1.81 in)	56 mm × 220 mm × 93 mm (2.20 in × 8.66 in × 3.65 in)	150 mm × 181 mm × 116 mm (5.90 in × 7.13 in × 4.55 in)
Weight	0.15 kg (0.33 lbs)	0.53 kg (1.17 lbs)	1.38 kg (3.04 lbs)
Sensor	1080P FHD	4K UHD	1080P FHD
Resolution	1080p, 720p, SD @ 30 fps	Main stream : 4K, 1080p, 900p, 720p @ 30 fps Sub stream : 720p, 480p, 172p @30 fps	1080p, 720p, SD @ 30 fps
Field of view	Horizontal: 87° Vertical: 50° Diagonal: 88°	Horizontal: 120° Vertical: 85° Diagonal: 126°	Horizontal: 55° Vertical: 31° Diagonal: 63°
Zoom	-	Digital : 4x	Optical : 20x Digital : 10x
Pan Tilt	-	Digital	±170° -30° to 90°
Pan Tilt speed	-	-	100°/sec 45°/sec
Focus	Fixed	Auto and manual	Auto and manual
Auto framing	-	Yes	-
Preset positions	-	10	• Remote: 10 • LAN: 255
Lens type	Glass	Glass	Glass
Low light performance	0.5 Lux	0.1 Lux	0.5 Lux
Audio			
Microphone	Omnidirectional mics	Omnidirectional mics	-
Input	-	-	3.5 mm
Output	-	-	HDMI, Ethernet, SDI
Echo cancellation	Yes	Yes	-
Video			
Output	USB 2.0	USB 3.0	USB 3.0, HDMI, Ethernet, SDI
Ethernet			
RJ-45	-	-	• 1GbE port • Power over Ethernet
Control Interface			
In Out	-	-	RS232, RS422, RS485 RS232
Power			
Voltage	5V	5V	12V
Compatibility			
Operating systems	Windows 7 (1080P/720P), Windows 8.1, Windows 10, macOS 10.10, Linux (UVC), and later versions		
BenQ displays	CP01K, CS01, SL02K, ST02, RP02, RM02K, RE01, and later models		
USB	Plug and play	Plug and play	Plug and play
Package Contents			
Included	• 1080P FHD webcam • Camera mount (built-in) • USB cable (built-in)	• 4K UHD conference cam • Remote control • Camera mount (built-in) • USB 3.0 Type-B	• 1080P FHD PTZ conference cam • Remote control • Camera mount (built-in) • USB 3.0 Type-B • Power supply

Headquarters
BenQ Corporation
16 Jihu Road, Neihu,
Taipei 114, Taiwan
Tel : +886-2-2727-8899
Fax : +886-2-2656-2438

Asia Pacific
BenQ Asia Pacific Corp.
12 Jihu Road, Neihu,
Taipei 114, Taiwan
Tel : +886-2-2727-8899
Fax : +886-2-2656-2438

China
BenQ (IT) Co., Ltd.
181 Zhuyuan Road, Suzhou
New District, Suzhou, China
Tel : +86-512-6807-8800
Fax : +86-512-6809-7010

North America
BenQ America Corp.
3200 Park Center Drive, Suite 150
Costa Mesa, CA 92626
U.S.A
Tel : +1-714-559-4900
Fax : +1-714-557-0200

Europe
BenQ Europe B.V.
Meerenakkerweg 1-17,
5652 AR Eindhoven,
The Netherlands
Tel : +31(0) 88-888-9200
Fax : +31(0) 88-888-9299

Latin and Central America
BenQ Latin America Corp.
8200 N.W. 33 Street, Suite 301
Miami, FL 33122
U.S.A.
Tel : +1-305-4211200
Fax : +1-305-4211201