



Connectivity

-

	Quantity
1 HDMI-1	1
2 HDMI-2	1
3 Display Port	1
4 HDBaseT(R)45)	1
5 3D Sync in	1
6 3D Sync out	1
7 Audio out (S/PDIF)	1
8 DC 12V Trigger	1
9 Audio out (mini jack)	1
10 LAN Port(R)45 for Network)	1
11 RS232 In (D-sub 9pin, male)	1
12 USB TypeA (SV.1.5A)	1
13 Wired Remote in (3.5 mini jack)	1
14 Wired Remote Out (3.5 mini jack)	1
15 IR Receiver(Front/Top)	2

Projection System	DLP Single
DMD type	0.47" 4K UHD
Native Resolution	3840 x 2160 pixels
Brightness	5500 ANSI Lumens
Contrast Ratio®	3,000,000:1
Display Color	30 Bits/1.07 Billion Colors
Aspect Ratio	Native 16:9
Light Source	Laser
Light Source Life®	Normal 20,000 hr/ECO 30,000 hr/SmartECO 30,000 hr

Throw Ratio	1.36 ~ 2.18 (Wide 95" ±3% @ 2.85m)
Zoom Ratio	1.6x
Lens shift	Yes
Keystone Correction	3D, Vertical & Horizontal +/- 30 degrees
Projection Offset	NA
Projection Size	60"~200"

Built-in Speaker	10W*1
------------------	-------

Security	Security Bar, Kensington lock
Feature	3D Keystone, Corner Fit, LAN Control, FW upgrade via USB, 360 degree projection, 24/7 operation

Resolution Support	VGA (640 x 480) to 4K UHD (3840 x 2160)
Horizontal Frequency	15K~135KHz
Vertical Scan Rate	23~240 Hz
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p
Video Compatibility	NA

Power Consumptions(Max/Normal/Eco)	Max: 520W / Normal: 405W / ECO: 270W
Standby Power consumption	Normal < 0.5Watts.
Power Supply	AC 100 to 240 V

Product Dimensions (WxHxD)	416 (W) x 351 (L)x 166 (H) mm
Product Weight	7.0 Kg+/- 200g

Noise Level(Normal/Eco)	39/40 dBA(normal) ; 32/33 dBA (ECO Mode) ; 37/38 dBA (Golf Mode)
Operating Temperature*	0 ~ 40°C

Accessories (Standard)	IG(4JJS202.001) Remote Control RCA011 (5JJJ606.001) AAA Batteryx2 Power Cord (1.8m) Warranty card (by Region)
Accessories (Optional)	Ceiling mount(5JAMI0.001) 3D Glasses DGD5

On Screen Display Language	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Farsi / Vietnamese/ (30 Languages)
----------------------------	---

* The Contrast is measure by Full On Full Off standard.

[illegible]

A: BenQ ceiling mount CMG3 (S.J.JAM10.061)
Ceiling mount screw M4
(Max. L = 25 mm; Min. L = 20 mm)

B: Third party mounting holes
Screw: M6 (Max. L = 8 mm)

Unit: mm

416 mm (W) x 166 mm (H) x 351 mm (D)

